

SPECIFICATIONS FOR WALL COVERING WITH FIBERGLASS CORE

SPECIFICATIONS		
Style	Ikat, Bamboo:	Chain Weave:
Fiber Content	Face: 80% vinyl, 20% fiberglass. Backing: 100% polyester, non-woven scrim backing.	
Width	72" wide (1.83 meters)	72" wide (1.83 meters)
Weight	18-20 oz / sq yd (0.61-0.68 kgs/m2)	21.5 oz / sq yd (0.73 kgs/m2)
Style	Basketweave, Kono:	Frost, Rib Weave:
Fiber Content	Face: 80% vinyl, 20% fiberglass. Backing: 100% polyester, non-woven scrim backing.	
Width	56" wide (1.42 meters)	56" wide (1.42 meters)
Weight	25 oz / sq yd (0.85 kgs/m2)	33 oz / sq yd (1.11 kgs/m2)
TESTS CONDUCTED		RESULT
COLORFASTNESS		Complies Cat VI Type III
Washability		Complies Cat VI Type II
Scrubability		Complies Cat VI Type III
Abrasion		Complies Cat III
Breaking Strength		Complies Cat VI Type III
Crocking		Complies Cat VI Type III
Stain Resistance		Complies Cat VI Type III
Tear test Complies		Cat VI Type III
Blocking Resistance		Complies Cat VI Type III
Coating Complies		Cat VI Type III
Cold Cracking		Complies Cat III
Heat Aging		Complies Cat VI Type III
Flame Spread *		Class A *
Smoke developed		Class A
Shrinkage Complies		Cat VI Type III

Please note: Individual test results are maintained at the manufacturing facility and are available if required. All tests listed above were performed by a certified independent laboratory.

* With Sprinklers